

PORTABLE HEAT PUMP LOCALIZABLE

MODEL
FSC25HP

Main features:

- Maximum cooling capacity: 7.1 kW
- Heating capacity (20 °C, 40% R.H.): 6.5 kW
- 2 speed cold air fan in cooling mode
- 2 speed hot air fan in heating mode
- Operating temperature:
 - in cooling mode: 7°C - 45°C
 - in heating mode: 10°C - 30°C
- Low noise
- High and low pressure switch alarm
- 20 litre condensate collection tank
- Fixed condensate drain predisposition
- Predisposition for condensate drain pump

Applications:

- Semi-enclosed spaces
- Garages, laboratories, workshops
- Industries
- Kiosks and large stands
- Leisure spaces



TECHNICAL DATA:

Maximum cooling capacity:	7.100 W
Maximum cooling capacity:	24.225 BTU/h
Heating capacity (20 °C, 40 % R.H.)	6.500 W
Heating capacity (20 °C, 40 % R.H.)	22.178 BTU/h
Power consumption in cooling (27°C 60% indoor):	2020 W
Power consumption in heating (20°C 40% indoor):	1940 W
Current consumption (27°C 60% indoor):	10 A
Cold air flowrate in cooling mode:	1.020 mc/h
Hot air flowrate in heating mode:	1.020 mc/h
Fan speed: - High speed	1.020 mc/h
- Low speed	800 mc/h
Hot air flowrate in cooling	1.800 mc/h
Cold air flowrate in heating	1.800 mc/h
Refrigerant R1234yf	1100 g
High efficiency compressor	Rotary
Indoor unit noise (at 3m in free field) at minimum speed	55 dB(A)
Dimensions WxDxH (mm):	790x620x1326
Condensate collection tank capacity	20 litres
Weight	100,6 Kg
Available voltages	230-240/1/50